Technical Specifications - CAST IRON SWING CHECK VALVES

Type of Valve

Swing Check Non Return Type, Bolted Cover, Renewable Seat-Rings

Materials of Construction:

- a. Body, Cover & Disc
- b. Hinge Bracket
- c. Hinge Pin
- d. Body Seat-Ring
- e. Disc Face-Ring
- f. Gasket
- g. Bolts & Nuts

Design

Testing Standards

Dimension

- Flange-to-Flange
- Flange Dimension & Drilling

Hydraulic test pressure:

- Rating
- Body
- Seat

Accessories

CI to IS 210 Fg 200/260

CI to IS 210 Fg 200/260

HT Brass or Stainless Steel

Bronze or Stailess Steel

Rubber, Bronze or Stainless Steel

Rubber

Carbon Steel to IS 1367 Cl 4.6/4.0 or ASTM Standard

IS 5312 (Part I) 2004 / BS:5153

IS 5312 (Part I)2004 / BS:5153

As per customer requirement

50 mm NB to 600 mm NB

PN 1.0 / 10 PN 1.6 / 16 15 Kg/Cm² 24 Kg/Cm² 10 Kg/Cm² 16 Kg/Cm²


Bypass arangement, Dash Pot & Counter Weight Arrangement (Size 300

& above)

Range

Part Name:

- 1. Body,
- 2. Cover
- 3. Disc
- 4. Hinge Bracket
- 5. Body Seat-Ring
- 6. Disc Face-Ring
- 7. Hinge Pin
- 8. Bolts & Nuts
- 9. Gasket



Note

- Description given is generalized, may vary as per requirement.
- Specifications given above are subject to change as per revisions in standards without notice.
- Quotations are based on customer's requirement and data. Customers are requested to send specific requirement for an offer.
- All sizes in millimeter

H. Sarker & Company Valves (P) Ltd.

Works: Phone: +91 33 2653 1214 / 0061 • eMail: hsblt09@gmail.com

Regd.Office: Ajit Sen Bhawan, 13 Crooked Lane, 2nd Floor, Kolkatta 700 069.

Phone:033-22109163

