### **Technical Specifications - CAST IRON BUTTERFLY VALVES (Flanged Type)**

### Type of Valve

#### **Materials of Construction:**

- a. Body
- b. Disc
- c. Drive Shaft
- d. Stub Shaft
- e. Shaft Bearing
- f. Body Seat
- g. Shaft Seal
- h. Disc Screw
- i. Indicating Plate
- i. Seat Retainer
- k. Hand Wheel
- I. Disc Seat
- m.End Cover Plate
- n. Thrust Pad

### Design

#### **Dimension**

- Face-to-Face
- Ends

### **Hydraulic test pressure:**

- Rating
- Body
- Seat

## Range

## Butterfly Valve Short Body, Worm Gear, Flanged Type

CI to IS 210 Gr. Fg 200/260

CI to IS 210 Gr. Fg 200/260

SS 410 SS 410

Bronze To 318 LTB 2

Stainless Steel Nitrile Rubber

Stainless Steel

MS to IS 2062 Gr A

Stainless Steel

CI to IS 210 Gr. Fg 200

Nitrile Rubber

MS to IS 2062 Gr. A

Bronze To 318 LTB 2

BS:5155 / Is 13095 / BSEN 593

BS:5155 / Is 13095


Flanged to customer requirement


PN 10 / 1.0 PN 16 / 1.6 15 Kg/Cm<sup>2</sup> 24 Kg/ Cm<sup>2</sup> 10 Kg/ Cm<sup>2</sup> 16 Kg/ Cm<sup>2</sup>

150 mm NB to 1200 mm NB

#### **Part Name:**

- 1. Body
- 2. Disc
- 3. Drive Shaft
- 4. Stub Shaft
- 5. Shaft Bearing (Bush)
- 6. Body Seat
- 7. Shaft Seal' O'Ring
- 8. Disc Screw
- 9. Disc Seat
- 10. Lever
- 11. Hand Wheel
- 12. Worm Gear (1/4 Turn)
- 13. Seat Retainer
- 14. End Cover Plate
- 15. Thrust Pad





#### Note

- Description given is generalized, may vary as per requirement.
- Specifications given above are subject to change as per revisions in standards without notice.
- Quotations are based on customer's requirement and data. Customers are requested to send specific requirement for an offer.
- All sizes in millimeter

# H. Sarker & Company Valves (P) Ltd.

Works: Phone: +91 33 2653 1214 / 0061 • eMail: hsblt09@gmail.com

Regd.Office: Ajit Sen Bhawan, 13 Crooked Lane, 2nd Floor, Kolkatta 700 069.

Phone:033-22109163

